

Reflectorless Total Station MTS-1002R series







1000m Reflectorless



Laser Plummet



USB Interface



Bluetooth*

Features:

- 1000m reflectorless measuring range & 7.5km range by single prism (1002R+)
- Dual large LCD display for face left/right measurement
- Bluetooth connection & USB data output
- Visible red laser plummet or optional optical plummet
- Alphanumeric keypad for quick entering of letters and numbers
- A variety of surveying programs: Coordinate measuring, Setting out points, Resection, Missing line measurement, Offset point, Remote elevation measurement, Area calculation, Angle repetition, Set out line, Set out curve, Set outroad
- Menu driven software with intuitive structure to maximize productivity
- Easy data upload and download via USB flash disk, Bluetooth or RS-232
- Expandable storage SD card (2G-16G Optional)





Dual Large LCD display & USB data output

Topcon Operation System

All specifications & design are subject to change without prior notification.

http://www.surveyinstru.com

Digital Line Company Limited

Specifications:

Model	MTS-1002R	MTS- 1002R+
Reflectorless measuring range Measuring range with single	600m 5km	1000m 7.5km
prism	JKIII	7.58111
Internal Memory / SD-Card	40000 Points / 2G-16G	
Blue tooth connection	Yes	
Telescope		
Image	Upright	
Objective aperture	45 mm	
Magnification	30 x	
Field of view	1° 30′	
Resolving power	4"	
Shortest focus distance	1.5 m	
Distance measurement		
Accuracy	2 mm + 2 ppm	
Measuring time	1.0s / 0.7s / 0.3s	
(Fine/Rapid/Tracking) Minimum reading	1 mm	
Distance units	m / ft	
Angle measurement	1117 10	
Minimum reading resolution	1" / 5" / 10"	
Angle accuracy	2"	
Angle units	100 % / 360° / 400 gon	
Compensator	Dual Axis, Electronic	
·	Туре	
Range	± 3°	
Display		
Dual LCD	Dual Disp	lay, illuminated
Laser plummet	1.4.5	. / 4 5
Accuracy Laser classification	± 1.5 mm / 1.5 m Class II, red laser	
	Class II, I	eu iaser
Power Supply Rechargeable battery type	7.2 V D	C NIMI
Operating time (Distance + Angle)	6 h	
Charger	100 / 240 V	
Vial sensitivity	100 /	210 0
Plate level vial	30" /	2 mm
Circular vial	8' / 2 mm	
Others		
Operating temperature	-20 °C -	+50 °C
IP-Class	IP	55
I/O-Port	RS-232, Blue	etooth, USB
Weight	6.5 kg	



Standard Outfit: Total station, 2 rechargeable batteries, charger, download software CD, tool Kit, English manual, plastic carry case.

Optional Accessories: Data Download Cable, USB Flash Disk

Operation system language: English, Spanish(Optional)

Colors available: Yellow